



CANARDO:

an on-sky experiment to validate MICADO SCAO design

Nicolas GALLAND, LESIA The MICADO SCAO team

October 19, 2020



N. Galland's position is funded by the WOLF ANR project

The MICADO instrument


Multi-AO Imaging Camera for Deep Observations, Germany-Netherlands-France-Austria consortium (lead: MPE)

Basic features

- First light imager
- Observing modes: imaging, astrometry, spectroscopy and high contrast imaging
- Diffraction limited in the near-IR thanks to SCAO and MCAO corrections

AO setup

- LGS+NGS MCAO system developed within MAORY consortium
- SCAO system developed within MICADO consortium
- Until MCAO is ready, MICADO will work with SCAO only with a dedicated optical relay
- When MAORY is in place later on, both SCAO and MCAO will be available



Credits: MICADO Consortium

CANARY facility at the 4.2 m William Herschel Telescope

CANARY bench

- Developed by Durham University and LESIA as an on-sky MOAO demonstrator and used to demonstrated various AO configurations (eg, two stage ELT like, off-axis LGS WFSing)
- Possibility to modify/add parts in this setup
- Very well known in the AO team at LESIA
- \rightarrow allow to limit the development effort





The CANARDO experiment


Goals

- Pyramid calibration test and on-sky validation
- test PWFS-AO control algorithms (optical gain, NCPA)
- RTC "stress test"

 \rightarrow CANARDO design at ELT scale, test performed under real turbulence conditions


Implementation

- Replace DM with ALPAO 4K DM (3228 actuators)
- Add MICADO WFS core including the MICADO SCAO pyramid component (96×96 subaps)
- Interface the MICADO RTC prototype



Development plan

Driven by the MICADO planning.





Additional experiment


contemplated with the WOLF project (French ANR-funded project to develop and test high performance WFS) : on-going discussions to optimize the effort to lead the two on-sky test campaigns

On-going work

Working with ALPAO 4K DM







RTC integration

- DM control and calibrations and WFS image processing & calibration
- real-time acquisition sequence validation (latency, jitter measurements...)